

LCD617/619 User Manual



Colour LCD screen with VGA & DVI inputs

LCD617 - 17" VGA Monitor

Incredible value and performance: a solid 17" display choice for reliability in home and office environments.

The highly-affordable LCD617 offers vivid image quality, convenient inputs for analogue and digital signals, crisp 1,000:1 typical contrast ratio, as well as built-in speakers for multimedia entertainment. With a sleek design and VESA compatible wall mounts that allow for a variety of mounting options, the LCD617 is designed perfectly for home use or multi-display office environments where cost is a consideration.

- > LED-backlit technology
- > Slim and sleek design
- > Economical and durable concern
- > Fast 3ms response time
- > Crisp 1,000:1 typical contrast ratio
- > Built-in speakers (3W x 2)
- > Tilt from -5 ° to +20 ° for optimal viewing
- > VESA standard wall mount
- > WEEE, RoHS, REACH certified



Sleek design with anti-glare display panel for superior viewing comfort



VESA standard wall mount allows for secure mounting



Built-in speakers provide easy access to multimedia applications



Tilt from -5 ° to +20 ° for optimal viewing

Specification

Panel	Panel Type Panel Size Max. Resolution Pixel Pitch Brightness Contrast Ratio Surface Treatments	LED-Backlit TFT LCD 17.0" (432 mm) SXGA 1280 x 1024 0.264 mm 250cd/m2 (Typical) 1,000:1 (Typical) Hard Coating (3H), Anti-glare treatment 170°/160° (Typical)
	Viewing Angle (H/V) Display Colour Response Time	170°/160° (Typical) 16.7M 3ms (GTG)
Frequency (H/V)		H: 30 kHz - 82 kHz V: 56 Hz - 75 Hz
Input	Analogue Digital	15-Pin D-Sub 24-Pin DVI-D
Audio	Audio In Speaker	1 x Stereo audio in for PC (audio jack, 3.5ø) 3W x 2
Power	Power Supply Power Requirements Consumption	Internal AC 100 - 240 V, 50 - 60 Hz < 22 W (On) < 0.5 W (Stand-by) < 0.5 W (Off)
Plug & Play	VESA	DCC 2B
Operating Conditions	Temperature Humidity	0 °C ~ 40 °C 10% ~ 85%
Storage Conditions	Temperature Humidity	-25 °C ~ 55 °C 10% ~ 85%
Mounting	VESA FPMPMI	Yes (100 x 100mm)
Tilt	Tilt	-5° ~ +20°
Dimensions	Product (W x H x D) Packaging (W x H x D)	384 x 358 x 195 mm (15.1" x 14.1" x 7.7") 417 x 397 x 136 mm (16.4" x 15.6" x 5.4")
Weight	Product Weight Packaged Product Weight	3.4 kg (7.5 lbs) 4.6 kg (10.1 lbs)
Regulation Approval	Certifications & Compliance	FCC, CB, CE, GOST-R, WEEE, RoHS, REACH
Accessories	Supplied	User manual, 15-Pin D-Sub cable, audio cable, AC power cord



LCD619 - 19" VGA Monitor

An excellent and affordable 19" display for home and office environments where quality, reliability and price are important considerations.

The valuable LCD619 delivers the high clarity and outstanding display performance that is well suited for the demands of modern office and home applications. Featuring 1,000:1 typical contrast ratio and built-in speakers, the slim modern design and convenient VESA compatible wall mounts make the LCD619 a perfect value choice for home and office environments.

- > LED-backlit technology
- > Slim and sleek design
- > Economical and durable concern
- > Fast 3ms response time
- > Crisp 1,000:1 typical contrast ratio
- > Built-in speakers (3W x 2)
- > Tilt from -5 ° to +20 ° for optimal viewing
- > Kensington® security socket
- > VESA standard wall mount
- > WEEE, RoHS, REACH certified



Sleek design with anti-glare display panel for superior viewing comfort



VESA standard wall mount allows for secure mounting



Built-in speakers provide easy access to multimedia applications



Tilt from -5 ° to +20 ° for optimal viewing

Specification

Panel	Panel Type Panel Size Max. Resolution Pixel Pitch Brightness Contrast Ratio Surface Treatments	LED-Backlit TFT LCD 19.0" (482 mm) SXGA 1280 x 1024 0.294 mm 250cd/m2 (Typical) 1,000:1 (Typical) Hard Coating (3H), Anti-glare treatment
	Viewing Angle (H/V) Display Colour Response Time	170°/170° (Typical) 16.7M 3ms (GTG)
Frequency (H/V)		H: 30 kHz - 82 kHz V: 56 Hz - 75 Hz
Input	Analogue Digital	15-Pin D-Sub 24-Pin DVI-D
Audio	Audio In Speaker	1 x Stereo audio in for PC (audio jack, 3.5ø) 3W x 2
Power	Power Supply Power Requirements Consumption	Internal AC 100 - 240 V, 50 - 60 Hz < 18 W (On) < 0.5 W (Stand-by) < 0.5 W (Off)
Plug & Play	VESA	DCC 2B
Operating Conditions	Temperature Humidity	0 °C ~ 40 °C 10% ~ 85%
Storage Conditions	Temperature Humidity	-25 °C ~ 55 °C 10% ~ 85%
Mounting	VESA FPMPMI	Yes (100 x 100mm)
Tilt	Tilt	-5° ~ +20°
Dimensions	Product (W x H x D) Packaging (W x H x D)	422 x 388 x 195 mm (16.6" x 15.3" x 7.7") 478 x 403 x 140 mm (18.8" x 15.9" x 5.5")
Weight	Product Weight Packaged Product Weight	3.9 kg (8.6 lbs) 5.8 kg (12.8 lbs)
Regulation Approval	Certifications & Compliance	FCC, CB, CE, GOST-R, WEEE, RoHS, REACH
Accessories	Supplied	User manual, 15-Pin D-Sub cable, audio cable, AC power cord

