



LCD343

While Stocks Last!

The LCD343 CCTV test monitor tests both CVBS and HD-TVI & AHD cameras. It quickly lets you set up and focus most cameras on the market and even gives simple co-axitron control functions too.

Measuring just 118mm wide and 90mm high the test monitor has a tough ABS case that is lightweight and easy to carry on your wrist using the free hook and eye arm strap provided. Supplied complete with a mini USB charger, the screen can operate for up to 6 working hours without recharging!

Ideal for the CCTV installer just starting out or as a spare to keep in your van, this low cost test monitor allows you to strap it your wrist and go. Great for when you need both hands free or when you're up a ladder fitting a CCTV camera.

Great Value 3-in-1 TVI, AHD & CVBS Test Monitor ... with Handy Wrist Strap!

- Handy Compact Size
- Portable 4.3" Display
- Tough ABS Case
- Wrist Strap
- Simple Co-axitron Control
- TVI, AHD & CVBS
- Approx Working Time up to 6hrs
- NTSC and PAL Compatible

TECHNICAL SPECIFICATION

HD-TVI 2.0 Input	Mini USB 5V DC 1A Input
CVBS Input	USB 12V DC Output
4.3" Screen 480x272 res	UK 3 Pin Charger Included
Co-axitron Control	Hook & Eye Wrist Strap Included
PAL / NTSC Switchable	2x Phono to BNC Connectors Included
3,7V DC Li-ion Battery 18650mAh	1x Video In / DC Power Out Cable
Up to 6 Hours working battery life	Plastic ABS Case
110-240V AC Input	H90 x W118 x D48 mm

Code	Description
LCD343	TVI, AHD & CCTV Test Monitor

LAST FEW LEFT !!



Handy Battery™ + Charger ... a 12V DC battery pack with a useful 2 Amp Output

- Checks for Voltage Drop
- Checks for Groundloops
- Use Two to Test Wire-Free Products
- Ideal for Use With Covert Cameras
- Ideal for Spare Battery
- Universal 2.1mm DC Plug



Use it for:

- ✓ Checking for Groundloops
- ✓ Checking for Volt Drop Issues
- ✓ Testing Cameras Whilst up a Ladder
- ✓ Powering Covert "Body-Worn" Cameras
- ✓ Benchtesting Wirefree Products & More!

SPECIFICATION BATTERY PACK

15.5 x 72 x 103mm	Connector - 2.1mm x 5.5mm DC plug
Capacity - 2000mAh	Lead Length 250mm
Nominal Voltage - 12V	Type - Ni-MH
Number of Cells - 10	Life - Approx 1000 Charge/Discharge
Weight - 302g	

CHARGER

UK Style Plug Adaptor
Input Voltage 230V
AC 50Hz
Secondary - 14V DC @ 120mA

Code	Description
BAT510	Battery Pack & Charger
BAT200	Battery Pack



Digital Multimeter

A great value digital multimeter with low battery indicator and AC Max range 200mV - 500V. Voltage measures DC range 200mV - 500V. Current range 2mA-5A. Resistance Max 2 mega ohms. See pg. 222

Code
TES552



Clamp Meter

This clamp multimeter is easy to use and perfect for most applications. Measuring voltage, current, resistance diodes and continuity. Comes supplied with test leads and storage case. Requires 1 x 9V battery (PP3). See pg. 222

Code
TES553



3-in-1 Voltage Tester

Indicates voltage range 110-150V, 220-330V and 380-500V AC. Determines if cables are live and helps to trace faults. Includes 760mm long cable. See pg. 222

Code
TO0832



3-in-1 Stud Detector

Self-calibrating 3-in-1 detector for detecting timber such as studs and ceiling joists, live AC wire and metal objects. LED and audible detection warning signals. Requires 1x9V (PP3) battery.

Code
TO0822



LAN Tester

Hand-held tester has connections suited for RJ11 & RJ45 cables. Twin speed. Master and remote box. Supplied with a zipped storage pouch. Requires 1x9V (PP3) battery. See pg. 218

Code
TO0835



Socket Tester

Identifies UK 13A mains socket wiring faults. 3 light indicators and durable design. Built-in 30mA RCD test function. Includes instructions. Certified and designed to BS EN 61010. Only suitable for UK 13A mains sockets. See pg. 222

Code
TO0830

Installer Details:

Installer Details:



Watch free videos on our new YouTube channel "System Q CCTV"

